



**F.O.G. CADDY
FILTRATOR
BATTERY**

SERVICE INSTRUCTIONS

These service instructions are intended as a guide to correct certain problems that may be encountered.

CAUTION: ALWAYS UNPLUG UNIT WHEN WORKING ON ELECTRICAL ITEMS.

PROBLEM	PROBABLE CAUSE	CORRECTIVE ACTION
1. Motor does not work	A) Battery not charged	1. Charge Battery
	B) Blown Fuse	2. Replace Fuse: Unscrew fuse holder cap located underneath the power unit. Remove the bad fuse and replace with the spare 15 AMP fuse provided with the unit. Replace the fuse holder cap by screwing the cap into place.
	C) Defective Switch	4. Replace Switch
	D) Defective Motor	5. Replace Motor
	E) Defective Battery	6. Replace Battery

NOTE: To replace any component inside the Power Unit other than the fuse requires the removal of the Power Unit Housing Cover.

PROBLEM	PROBABLE CAUSE	CORRECTIVE ACTION
1. Lack of Suction or Discharge	A) Clogged Screen	1. If this happens during operation, reverse the flow of the oil.
	B) Hardened oil in pump or elsewhere	2. Place unit near heat source to loosen the hardened oil.
	C) Loose Fittings	3. Check tightness of pump nipple/sockets and screen.
	D) Cracked and /or swollen Hose	4. Replace Hose